

Karta produktu

Włóknina filtracyjna "sucha" w rolkach

PSF-PR123-...
Typy włóknin:
PR123 - - -
1 2 3

- 1** – Rozmiar rolki [m]; np. **1,6x35m, 2x20m**
- 2** – Klasa filtracji [EN779]; np. **G2, G3, G4, M5**
- 3** – Gramatura [g/m²]; np. **150, 200, 220**


Materiał filtracyjny i parametry:

Typ włókniny	Gramatura	Klasa filtracji	Grubość	Przepustowość	Chłonność pyłu	Temperatura pracy
[-]	[g/m ²]	[EN779:2012]	[mm]	[m ³ /h/m ²]	[g/m ²]	[°C]
PR123-G2	130-150	G2	10-12	5000-5500	390	100
PR123-G3-150	150-160	G3	6-8	5300-5600	290	100
PR123-G3-200	200	G3/G4	10-12	7000-7200	350	100
PR123-G4-200	200	G4	16-18	5300-5400	450	100
PR123-G4-220	220	G4	22	5400-5500	520	100
PR123-M5-SUFIT	300	M5	22	900	430	100
Materiał wykonania:	100% poliester, budowa progresywna					
Odporność na wilgoć:	100%			Klasa palności:		F1 9DIN53438)

